



Safety Data Sheet

Page 1 of 10

LOCTITE LB 771 known as LOCTITE NICKEL ANTI-SEIZE
771

SDS No. : 319450

V001.7

Date of issue: 22.05.2025

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE LB 771 known as LOCTITE NICKEL ANTI-SEIZE 771

Intended use: Lubricant

Supplier:

Henkel Australia Pty Ltd
135-141 Canterbury Road
Kilsyth, Victoria, 3137
Australia

Phone: +61 (3) 9724 6444

**Emergency Telephone for
Chemical Accidents:** 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>
Skin sensitizer	Category 1
Carcinogenicity	Category 2
Target Organ Systemic Toxicant - Repeated exposure	Category 1
Acute hazards to the aquatic environment	Category 2
Chronic hazards to the aquatic environment	Category 3

Hazard pictogram:



Signal word:

Danger

LOCTITE LB 771 known as LOCTITE NICKEL ANTI-
SEIZE 771

Hazard statement(s):	H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H372 Causes damage to organs through prolonged or repeated exposure. H401 Toxic to aquatic life. H412 Harmful to aquatic life with long lasting effects.
Precautionary Statement(s):	
Prevention:	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe mist/vapours. P264 Wash hands thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P302+P352 IF ON SKIN: Wash with plenty of water. P308+P313 IF exposed or concerned: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.
Storage:	P405 Store locked up.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Distillates (petroleum), hydrotreated heavy paraffinic (not cmr)	64742-54-7	10- < 30 %
Nickel	7440-02-0	10- < 30 %
Graphite	7782-42-5	< 10 %
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO	64742-65-0	< 10 %
Residual oils (petroleum), hydrotreated, <3% DMSO	64742-57-0	< 10 %
Mineral oil		1- < 10 %
aluminium powder (stabilised)	7429-90-5	< 10 %

Section 4. First aid measures

Ingestion:	Rinse mouth, do not induce vomiting, consult a doctor.
Skin:	Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.
Eyes:	Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.
Inhalation:	Move to fresh air.
First Aid facilities:	Eye wash Normal washroom facilities

Medical attention and special treatment: Treat symptomatically.

Section 5. Fire fighting measures

Suitable extinguishing media: Foam, extinguishing powder, carbon dioxide.

Decomposition products in case of fire: carbon oxides.
Irritating organic vapours.

Special protective equipment for fire-fighters: Wear protective equipment.
Wear self-contained breathing apparatus.

Section 6. Accidental release measures

Personal precautions: Danger of slipping on spilled product.
Wear impervious gloves and chemical splash goggles.

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: Soak up with inert absorbent.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Precautions for safe handling: Ensure that workrooms are adequately ventilated.

Conditions for safe storage: Keep container tightly sealed.
Store in a dry place.

Section 8. Exposure controls / personal protection

National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
Oil mist, refined mineral 64742-54-7			5				
NICKEL, POWDER 7440-02-0			1				
NICKEL, METAL 7440-02-0			1				
GRAPHITE (ALL FORMS EXCEPT FIBRES) (RESPIRABLE DUST) (NATURAL & SYNTHETIC) 7782-42-5	Respirable dust.		3				
Oil mist, refined mineral 64742-65-0			5				

Oil mist, refined mineral 64742-57-0			5				
ALUMINIUM (METAL DUST) 7429-90-5	Dust.		10				
ALUMINIUM (WELDING FUMES) (AS AL) 7429-90-5	Fume.		5				
ALUMINIUM, PYRO POWDERS (AS AL) 7429-90-5			5				

Engineering controls:	Ensure good ventilation/extraction.
Eye protection:	Wear chemical goggles.
Skin protection:	Use of protective coveralls and long sleeves is recommended. Protective gloves made of rubber.
Respiratory protection:	If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance:	Dark gray / grey liquid
Odor:	Hydrocarbon-like
Flash point:	> 240 °C (> 464 °F)
Density:	1.1 g/cm ³
Solubility in water:	Insoluble

Section 10. Stability and reactivity

Stability:	Stable under normal conditions of temperature and pressure.
Conditions to avoid:	Avoid ignition sources where dust is produced.
Incompatible materials:	Strong oxidizing agents. Nickel powder can react explosively with substances such as ammonium nitrate, perchlorates, phosphorus, selenium, sulfur, etc...
Hazardous decomposition products:	In case of fire toxic gases can be released. Irritating organic vapours. Oxides of carbon.

Section 11. Toxicological information

LOCTITE LB 771 known as LOCTITE NICKEL ANTI-
SEIZE 771

Health Effects:

Ingestion:

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Skin:

May cause skin sensitization.

May cause skin irritation.

Eyes:

May cause eye irritation.

Inhalation:

Inhalation of dust generated by this material may cause respiratory tract irritation.

Chronic effects:

Nickel

7440-02-0:

Skin damage and respiratory dysfunctions after sensitisation; contact dermatitis, contact urticaria, allergic rhinitis and allergic asthma; active pneumonia, hyperplasia of the macrophages, alveolar proteinosis, fibrosis, hyperplasia of the bronchial lymph nodes and atrophy of the olfactory epithelium; carcinogenic potential, the lungs and nose are the target organs of the carcinogenicity of nickel and nickel compounds. Soluble Ni is quickly resorbed in the respiratory tract, percutaneous resorption is regarded as negligible.

Carcinogenicity:

Suspected of causing cancer.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Distillates (petroleum), hydrotreated heavy paraffinic (not cmr) 64742-54-7	LD50 LC50 LD50	> 5,000 mg/kg > 5.53 mg/l > 5,000 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
Nickel 7440-02-0	LD50	> 9,000 mg/kg	oral		rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Graphite 7782-42-5	Acute toxicity estimate (ATE) LC50	> 5,000 mg/kg > 2 mg/l	oral inhalation	4 h	rat	Expert judgement OECD Guideline 403 (Acute Inhalation Toxicity)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	LD50 LC50 LD50	> 5,000 mg/kg > 5.53 mg/l > 5,000 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
Residual oils (petroleum), hydrotreated, <3% DMSO 64742-57-0	LD50 LC50 LD50	> 5,000 mg/kg > 5.53 mg/l > 5,000 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
aluminium powder (stabilised) 7429-90-5	LD50 LC50	> 15,900 mg/kg > 5 mg/l	oral inhalation	4 h	rat rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) not specified

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Graphite 7782-42-5	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	not irritating	24 h	rabbit	not specified
aluminium powder (stabilised) 7429-90-5	not irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Graphite 7782-42-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
aluminium powder (stabilised) 7429-90-5	not irritating		rabbit	FDA Guideline

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Graphite 7782-42-5	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
aluminium powder (stabilised) 7429-90-5	not sensitising	Draize Test	guinea pig	Draize Test

LOCTITE LB 771 known as LOCTITE NICKEL ANTI-
SEIZE 771

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Graphite 7782-42-5	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	negative negative	in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
aluminium powder (stabilised) 7429-90-5	positive positive negative	in vitro mammalian cell micronucleus test in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	without without with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test) equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
aluminium powder (stabilised) 7429-90-5	negative ambiguous	oral: gavage oral: gavage		rat rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Graphite 7782-42-5	NOAEL=ca. 813 mg/kg	oral: feed	daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Section 12. Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

Ecotoxicity:

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Distillates (petroleum), hydrotreated heavy paraffinic (not cmr) 64742-54-7	LL50	> 100 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Distillates (petroleum), hydrotreated heavy paraffinic (not cmr) 64742-54-7	EL50	> 10,000 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Distillates (petroleum), hydrotreated heavy paraffinic (not cmr) 64742-54-7	NOELR	100 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Nickel 7440-02-0	LC50	Toxicity > Water solubility	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Nickel 7440-02-0	EC50	Toxicity > Water solubility	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Graphite 7782-42-5	LC50	Toxicity > Water solubility	Fish	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Graphite 7782-42-5	EC50	Toxicity > Water solubility	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Graphite 7782-42-5	EC50	Toxicity > Water solubility	Algae	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Graphite 7782-42-5	NOEC	Toxicity > Water solubility	Algae	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Graphite 7782-42-5	EC50	Toxicity > Water solubility	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	LC50	> 5,000 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	EC50	> 1,000 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	NOELR	100 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Residual oils (petroleum), hydrotreated, <3% DMSO 64742-57-0	LL50	> 100 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Residual oils (petroleum), hydrotreated, <3% DMSO 64742-57-0	EL50	> 10,000 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Residual oils (petroleum), hydrotreated, <3% DMSO 64742-57-0	NOELR	100 mg/l	Algae	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

LOCTITE LB 771 known as LOCTITE NICKEL ANTI-
SEIZE 771

Mineral oil	LC50	> 100 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Mineral oil	EC50	> 10,000 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Mineral oil	EC50	> 100 mg/l	Algae	72 h	Scenedesmus quadricauda	OECD Guideline 201 (Alga, Growth Inhibition Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Distillates (petroleum), hydrotreated heavy paraffinic (not cmr) 64742-54-7	not readily biodegradable.	aerobic	31 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO 64742-65-0	not readily biodegradable.	aerobic	6 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Mineral oil	not readily biodegradable.	aerobic	31 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

Section 13. Disposal considerations

Waste disposal of product:	Collection and delivery to recycling enterprise or other registered elimination institution.
Recommended cleanser:	Solvent naphtha
Disposal for uncleaned package:	Dispose of in accordance with local and national regulations.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information:	Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).
------------------------------	--

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

SUSMP Poisons Schedule	None
------------------------	------

Section 16. Other information

Abbreviations/acronyms:	GHS: Globally Harmonized System IATA-DGR: International Air Transport Association – Dangerous Goods Regulations IMDG: International Maritime Dangerous Goods code STEL - Short term exposure limit TWA - Time weighted average AIIC - Australian Inventory of Industrial Chemicals (AIIC) AICIS - Australian Industrial Chemicals Introduction Scheme
Reason for issue:	Reviewed MSDS. Reissued with new date. involved chapters: 1-16
Date of previous issue:	12.05.2022
Disclaimer:	The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material. The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet. This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.